

In The Claims

Please amend the claims as follows:

What is claimed is:

1-27 (canceled)

28. (previously presented) A stereomicroscope comprising:

a binocular tube (1),

a microscope body (4) for passing two stereoscopic observation beam paths (3a, 3b), the microscope body (4) comprising an incident light illumination system or connection therefor and an illumination beam path (34) separate from the observation beam paths such that when a stereo lens (6) is selected the illumination beam path passes through the lens (6),

a microscope holder (14) that is connected to a displaceable focus-adjusting mechanism (9), the focus-adjusting mechanism (9) in turn being fastened to a stand (13),

a beam splitter (2a) used to combine the two stereoscopic observation beam paths (3a, 3b) into a common beam path (3c), wherein the axes of the two observation beam paths (3a, 3b) entering into the binocular beam splitter (2a) and the axis of the beam path (3c) emerging from the binocular beam splitter (2a) are parallel to each other, and the axis of the emerging beam path (3c) is disposed at displacement (Vs) from a symmetry axis of the two entering observation beam paths (3a, 3b),

a system for coupling an illumination beam path (34) into the beam path (3c) emerging from the binocular beam splitter (2a),

a carrier (12) bearing the microscope body (4) and being displaceable obliquely relative to a displacement direction of the focus-adjusting mechanism (9) to compensate for said displacement (V_s),

a switching device (5) held on said holder (14) and provided with mounts for at least one stereo lens (6) and at least one compound lens (7), wherein by actuating the switching device (5) each of the lenses (6, 7) can selectively be brought over an object (8) and both the stereo lens (6) and the compound lens (7) can be placed over the object (8) parfocally and parcentrically,

a gear (10) which, depending on the position of the switching device (5), automatically brings about the displacement of the carrier (12) to compensate for displacement (V_s),

wherein the binocular beam splitter (2a) is disposed between the carrier (12) and the compound lens (7).

29. (previously presented) A stereomicroscope as claimed in claim 28 wherein an incident light illumination system is configured as said incident fluorescent light illumination system fitted with exciter and blocking filters (19a, 19b) .

30-31 . (canceled)

32. (previously presented) A stereomicroscope as defined in claim 28 wherein a displacement range of the carrier (12) corresponding to the displacement (V_s) comprises path components corresponding to displacement components (V_{sx} , V_{sy}) in at least two directions (X/Y) of a plane.

33. (previously presented) A stereomicroscope as defined in claim 28 wherein the displacement range of the carrier (12) corresponds to a displacement range of the microscope body (4) such that the two stereoscopic observation beam paths (3a, 3b) can selectively

a) pass through the stereo lens (6) or

b) coincide with the inlet axes of the binocular beam splitter (2a).

34. (previously presented) A stereomicroscope as defined in claim 28 wherein the axes of the observation beam paths (3a, 3b) and the axis of the stereo lens (6) are parallel, and the axes of the observation beam paths (3a, 3b) are mirror symmetrical to each other with respect to a plane in which also lies the axis of the stereo lens (6).

35. (previously presented) A stereomicroscope as defined in claim 33 wherein a) the axes of the stereoscopic observation beam paths (3a, 3b) and the axis of the stereo lens (6) do not lie in a common plane.

36. (previously presented) A stereomicroscope as defined in claim 28 wherein the switching device (5) is configured as a rotatable turret or as a slider, the direction of movement of which is essentially parallel to a common plane of the two observation beam paths (3a, 3b).

37. (previously presented) A stereomicroscope as defined in claim 28 wherein the holder (14), the gear (10), the displaceable carrier (12) and the switching device (5) form with the lens mounts and the binocular beam splitter (2a), a single unit which selectively can be connected to or detached from the microscope body (4).

38. (previously presented) A stereomicroscope as defined in claim 28 wherein the holder (14), the gear (10), the displaceable carrier (12) and the switching device (5) form with

the lens mounts and the binocular beam splitter (2a) and the illumination coupling-in system, a single unit which selectively can be connected to or detached from the microscope body (4).

39. (currently amended) A stereomicroscope as defined in claim 28, wherein the compound lens (7) from a group of such lenses can be selectively and interchangeably connected with the one of the switching device (5), the binocular beam splitter (2a), and the illumination coupling-in device system (15).

40. (previously presented) A stereomicroscope as defined in claim 28, wherein the mount for the compound lens (7) comprises a fine focusing system (11).

41. (previously presented) A stereomicroscope as defined in claim 28, wherein at least one of the mounts comprises an adjustable system for adjusting the lens (7) in a direction across the lens axis.

42. (previously presented) A stereomicroscope as defined in claim 28, wherein the stereo lens (6) can be selected from a group of stereo lenses or switched with a lens from such a group.

43. (previously presented) A stereomicroscope as defined in claim 28, wherein the switching device (5) can be rotated through an angle of 360 degrees and is provided with latches.

44. (previously presented) A stereomicroscope as defined in claim 28 wherein the holder (14) is L shaped, the short part of the "L" being fastened to the focus adjusting mechanism (9).

45-46. (canceled)

47. (previously presented) A stereomicroscope as defined in claim 38, wherein the system for illumination in-coupling (15) comprises a mirror (42) and ~~for~~ a second beam splitter (43) disposed between the binocular beam splitter (2a) and the compound lens (7).
48. (previously presented) A stereomicroscope as defined in claim 47, wherein the system for illumination in-coupling (15) comprises an adjustable mirror (42).
49. (previously presented) A stereomicroscope as defined in claim 47 wherein the second beam splitter (43) is configured as a neutral tint beam splitter.
50. (previously presented) A stereomicroscope as defined in claim 47 wherein the second beam splitter (43) is configured as a dichroic beam splitter.
51. (previously presented) A stereomicroscope as defined in claim 47 wherein the second beam splitter (43) is adapted to the filter properties of the exciter and blocking filters (19a, 19b) and can be selected from a group of beam splitters or switched with a beam splitter from such a group.
52. (previously presented) A stereomicroscope as defined in claim 47, wherein the second beam splitter (43) is configured as a flat component with main boundary surfaces extending parallel to the beam splitter surface.
53. (previously presented) A stereomicroscope as defined in claim 28, wherein ~~first~~ beam splitter (2a) is a first beam splitter in the form of Y prism (2b).
54. (previously presented) A stereomicroscope as defined in claim 53 the carrier (12) and the gear (10) permit the microscope body (4) to be displaced exclusively in a single spatial

direction (Y) for the purpose of introducing a displacement (V_{sy}) of the stereo lens (6) in this spatial direction (Y).

55. (previously presented) A stereomicroscope as defined in claim 54, wherein the displacement range of the carrier (12) corresponds to a displacement range of the microscope body (4) such that both stereoscopic observation beam paths (3a, 3b) pass through the stereo lens (6) parcentrically to the compound lens, wherein the axes of the observation beam paths (3a, 3b) and the axis of the stereo lens (6) are parallel, and the axes of the observation beam paths (3a, 3b) are mirror symmetrical with each other with respect to a plane in which also lies the axis of the stereo lens (6).

56. (previously presented) A stereomicroscope as defined in claim 28, wherein it is equipped as a surgical microscope without lens carrier and that for the switching device (5) a remotely controllable electric drive is provided to bring about remotely controlled switching between the two lenses (6,7).

57. (previously presented) A stereomicroscope as defined in claim 28, wherein the gear (10) comprises at least one gear wheel (23a, 23b) and one gear rack (24) or a crank mechanism (35) with a cam (36) which are disposed or configured so that during a displacement they bring about a displacement (V_s) with displacement components (V_{sx} , V_{sy}) in two spatial directions of a plane.

58. (previously presented) An element for a stereomicroscope comprising a microscope holder (14), a gear (10), a carrier (12) for a microscope body that can be displaced relative to the holder (14) and a switching device (5) supported on the holder (14) and provided

with lens mounts for at least one stereo lens (6) and at least one compound lens (7), as well as with a binocular beam splitter (2a), wherein all said components form a single unit which can selectively be connected with or detached from a focus adjusting mechanism (9) of a stand (13) and a microscope body (4).

59. (previously presented) The stereomicroscope of claim 28 wherein the illumination beam path is parallel to the to the observation beam paths (3a, 3b).